

WHAT IS CLAIMED IS:

1. An electrical connector having a housing comprising:
 - a first housing element provided with at least a first connection portion that is either male or female;
 - 5 and
 - a second housing element provided with at least one second connection portion that is either female or male, respectively, suitable for co-operating with the first connection portion;
- 10 at least one of the first and second connection portions including at least one elastically deformable tab made integrally with the corresponding connection portion in the thickness of a cylindrical of said connection portion, which wall defines a single cavity
- 15 that presents, in cross-section, at least one side in the form of a straight line segment, the tab extending, in cross-section, along said side, wherein the tab presents, in cross-section, a width that is greater than half the length of said side.
- 20
2. A connector according to claim 1, wherein the cylindrical wall presents, in cross-section, two sides forming substantially parallel straight line segments.
- 25
3. A connector according to claim 2, wherein the cylindrical wall presents a cross-section that is substantially rectangular.
4. A connector according to claim 1, wherein said at
- 30 least one elastically deformable tab extends over a major fraction of the height of the connection portion.
5. A connector according to claim 1, wherein the elastically deformable tab presents a free end that is
- 35 remote from the base of the corresponding connection portion.

6. A connector according to claim 1, wherein said at least one tab includes at least one portion in relief on a face that comes to bear against the other connection portion.

5

7. A connector according to claim 6, in which said at least one tab has a top edge, wherein said at least one portion in relief is adjacent to said top edge or is situated in the proximity thereof.

10

8. A connector according to claim 6, wherein the portion in relief is in the form of a rib extending transversely to the longitudinal direction of the tab.

15

9. A connector according to claim 8, wherein the rib extends over the entire width of the tab.

20

10. A connector according to claim 1, wherein one of the connection portions has two facing elastically deformable tabs.

25

11. A connector according to claim 1, wherein each tab is substantially plane in shape, preferably being rectangular.

30

12. A connector according to claim 1, wherein the elastically deformable tab presses against a wall of the other connection portion that is substantially plane.

35

13. A connector according to claim 1, wherein at least one of the connection portions includes two adjacent cavities separated by an intermediate wall.

14. A connector according to claim 1, wherein the housing elements are made of an electrically conductive material so as to provide shielding for the housing.

15. A connector according to claim 14, wherein the housing elements are made of metal, in particular of aluminum.

5 16. A connector according to claim 1, wherein the cylindrical wall presents a thickness that is less than 1 cm.